


Notes:

1. Reinforced with two layers of 10M rebar on 250mm centres both ways one layer at each face.
2. Min. concrete cover: 25mm.
3. Min. concrete strength: 34.5MPa.
4. 6-8% air entrainment.
5. Max. concrete slump while pouring: 75mm.
6. Additional diagonal reinforcing, 4 @ each corner, 15M bar x 2000mm length.
7. 25mm chamfer on top exposed edge.
8. 25mm pvc pipe sleeves as shown for 19mm bolts on the vertical.
9. Box designed to ASTM C1433M for depth of earth cover.
10. 50mm PVC pipe sleeves for horizontal bolts.

 <p>The LANGLEY CONCRETE Group of Companies</p>	<p>DESCRIPTION:</p> <p style="text-align: center;">2400x1200 Box Endwall City of Abbotsford-Box Installations</p>	<p>DRAWN BY: JAO</p>	<p>ORIGIN: LC&T</p>
		<p>SCALE: 1:50</p>	<p>DRAWING NO.:</p>
		<p>DATE: 00/03/10</p>	<p>BHW-2.0</p>
<p>LANGLEY (604)533-1656 VICTORIA (250) 478-9581 CHILLIWACK 1-800-667-9600</p>		<p><small>This drawing is the property of the Langley Concrete Group of Companies. All information contained herein is confidential and may not be used in whole or in part without written permission from the owner.</small></p>	