



Notes:

1. Reinforced Ø750 x 900 mm catch basin manufactured to meet ASTM C 478 specification.
2. Ø750 x 900 mm Catch basin manufactured in accordance with MMCD specification.
3. Unit c/w 152 mm thick Lid as shown.
4. Unit c/w 152 mm thick base as shown.
5. Unit c/w Ø225 mm core as shown.
6. Screened weeping hole provided as shown.
7. Unit c/w 2-Ø16 mm galvanized rods for trapping hood assembly as shown.
8. Approximate mass:
 - CB Barrel: 635 kg/m.
 - Lid: 225 kg.
 - Spacer Ring: 35 kg.
9. Minimum concrete strength: 27.6 MPa.
10. Minimum rebar yield strength: 414 MPa.
11. Minimum WWF yield strength: 448 MPa.
12. All dimensions are in millimeters.



DESCRIPTION:

Ø750x900 C478
MMCD Style
Catchbasin

www.langleyconcretegroup.com

DRAWN BY:	KS	ORIGIN:	CHWK
CHK BY:	JAO/JDB	DWG NO:	CB750-MMCD
DATE:	MAR/01/2010	REV DATE:	1. JULY/15/2010
SCALE:	1:20		

This drawing is the property of the Langley Concrete Group of Companies. All information contained herein is confidential and may not be used in whole or in part without written permission from the owner.