



Langley Concrete Group - Mainland MH Dimensions				
MH Diameter [A] (mm)	Wall [B] (mm)	Joint Height [C] (mm)	Lid Thickness [D] (mm)	Base Thickness [E] (mm)
1050	121	70	152	152
1200	146	108	152	152
1350	140	108	254	203
1500	152	121	260	203
1650	184	127	260	203
1800	178	127	280	203
2400	229	130	280	203
3050	279	152	280	203

Notes:

- Manhole manufactured to the following specifications:
 - ASTM C 478
 - CSA A257.3
- Manhole supplied with ©Tylex SuperSeal Gasket joints.
- Gaskets can be employed for a 13 Psi rated sealed joint.
- Manhole c/w aluminum ladder rungs.
- Unit c/w lifting inserts as required.
- Minimum WWF yield strength: 448 MPa.
- Minimum rebar yield strength: 414 MPa.
- Minimum concrete strength: 27.6 MPa.
- All dimensions are in millimeters.



DESCRIPTION:

Ø1050-3050 mm
Superseal Gasketed
Manhole Details

www.langleyconcretegroup.com

DRAWN BY:	KS	ORIGIN:	CHWK
CHK BY:	JAO/TM	DWG NO:	SSM-1
DATE:	NOV/10/2009	REV DATE:	1. JUNE/29/2011
SCALE:	1:20		

This drawing is the property of the Langley Concrete Group of Companies. All information contained herein is confidential and may not be used in whole or in part without written permission from the owner.