



Notes:

1. 4212-8 mm spacing, Oil interceptor manufactured to meet AASHTO HS20 live loading.
2. Unit dimensions are 4.0 x 2.1 x 2.0 m.
3. Reinforced concrete lid manufactured for AASHTO HS20 live loading.
4. Unit c/w rough cores for inlet/outlet as required.
5. Unit c/w 2-Ø635 mm opening for accesses as shown.
6. Oil interceptor c/w 102 mm thick concrete baffles as shown.
7. Unit has a maximum 9,740 liter [9.74 m³] capacity.
8. Unit c/w lifting inserts as required.
9. Unit c/w ladder rungs upon request.

10. Unit design to:

- Temp.: 0°C.
- Oil S.G.: 0.85.
- Influent oil: 100 mg/l.
- Effluent oil <= 15 mg/l.
- Max. flow: 48.3 l/sec.

11. PVC required by design, installed by others in field
12. Design can be modified for specific application, please contact LCG sales office.

13. Approximate weight:

- Top section: 14,870 kg.
- Bottom section: 16,810 kg.

14. Minimum rebar yield strength: 414 MPa.

15. Minimum concrete strength: 35 MPa.

16. All dimensions are in millimeters.



The LANGLEY CONCRETE Group of Companies

DESCRIPTION:

4212 Coalescing Plate Oil Interceptor
8 mm Spacing

www.langleyconcretegroup.com

DRAWN BY: KS ORIGIN: CHWK

CHK BY: SW/JAO DWG NO: 4212-COI-8

DATE: OCT/15/2009 REV DATE: 2. OCT/19/2010

SCALE: 1:50

This drawing is the property of the Langley Concrete Group of Companies. All information contained herein is confidential and may not be used in whole or in part without written permission from the owner.