



Section View

Notes:

1. Reinforced Ø750 x 900 mm catch basin manufactured to meet ASTM C 478 specification.
2. Ø750 x 900 mm Catch basin conforms to MOT specifications, dwg SP582-02.01.
3. Unit c/w 152 mm thick Lid as shown.
4. Unit c/w 152 mm thick base as shown.
5. Unit c/w Ø225 mm core as shown.
6. Unit c/w 2-Ø16 mm galvanized pins for trapping hood assembly as shown.
7. Approximate mass:
 - CB Barrel: 635 kg/m.
 - Lid: 225 kg.
 - Spacer Ring: 35 kg.
8. Minimum concrete strength: 30 MPa.
9. Minimum rebar yield strength: 414 MPa.
10. Minimum WWF yield strength: 448 MPa.
11. All dimensions are in millimeters.



Quality Assurance of products manufactured by The Langley Concrete Group has been verified by the following third party certification programs:



The **LANGLEY CONCRETE** Group of Companies

www.langleyconcretegroup.com

DESCRIPTION:

Ø750X900 C478
MOT Style
Catch Basins

DRAWN BY: KS	JOB NO.: N/A
CHK BY: JAO/JDB	DWG NO: CB750-MOT
DATE: Mar. 1, 2010	REV. BY:
SCALE: 1:20	
<small>This drawing is the property of the Langley Concrete Group of Companies. All information contained herein is confidential and may not be used in whole or in part without written permission from the owner.</small>	
LCG Products are held to the governing ASTM, and CSA specification & tolerances.	

LANGLEY (604) 533-1656 VICTORIA (250) 478-9581 CHILLIWACK 1-800 667-9600