



**Notes:**

1. Recommended for parking lot applications as shown.
2. Min. concrete strength: 30 MPa.
3. Comes with 200mm core, 75mm weeping hole.
4. Available with trapping hood pins upon request.
5. Manufactured to ASTM C478 standard.
6. Approx. weight: 550 kgs.
7. All dimensions are in millimeters.

<p>Quality Assurance of products manufactured by The Langley Concrete Group has been verified by the following third party certification programs:</p>	<p>The <b>LANGLEY CONCRETE</b> Group of Companies www.langleyconcretegroup.com</p>	<p>DESCRIPTION:</p> <p style="text-align: center;"><b>Ø600x1000</b> Catch Basin- No Base</p>	DRAWN BY: JAO	JOB NO.: N/A
			CHK BY:	DWG NO: CB-1a NB
			DATE: Apr. 8, 2010	REV.A JZ, AUG20,2018
			SCALE: 1:16	
			<p><small>This drawing is the property of the Langley Concrete Group of Companies. All information contained herein is confidential and may not be used in whole or in part without written permission from the owner.</small></p>	
<p>LANGLEY (604) 533-1656 VICTORIA (250) 478-9581 CHILLIWACK 1-800 667-9600</p>			<p>LCG Products are held to the governing ASTM, and CSA specification &amp; tolerances.</p>	