



Notes:

1. Reinforced  $\text{Ø}750 \times 900$  mm catch basin manufactured to meet ASTM C 478 specification.
2.  $\text{Ø}750 \times 900$  mm Catch basin manufactured in accordance with MMCD specification.
3. Unit c/w 152 mm thick Lid as shown.
4. Unit c/w 152 mm thick base as shown.
5. Unit c/w  $\text{Ø}225$  mm core as shown.
6. Screened weeping hole provided as shown.
7. Unit c/w 2- $\text{Ø}16$  mm galvanized rods for trapping hood assembly as shown.
8. Approximate mass:
  - CB Barrel: 635 kg/m.
  - Lid: 225 kg.
  - Spacer Ring: 35 kg.
9. Minimum concrete strength: 30 MPa.
10. Minimum rebar yield strength: 414 MPa.
11. Minimum WWF yield strength: 448 MPa.
12. All dimensions are in millimeters.

<p>Quality Assurance of products manufactured by The Langley Concrete Group has been verified by the following third party certification programs:</p>	<p>The LANGLEY CONCRETE Group of Companies www.langleyconcretegroup.com</p>	DESCRIPTION:	DRAWN BY: KS	JOB NO.: N/A
		$\text{Ø}750 \times 900$ C478 MMCD Style Catch Basin	CHK BY: JAO/JDB	DWG NO: CB750-MMCD
			DATE: Mar. 1, 2010	
			SCALE: 1:20	
<p>LANGLEY (604) 533-1656 VICTORIA (250) 478-9581 CHILLIWACK 1-800 667-9600</p>			<p>This drawing is the property of the Langley Concrete Group of Companies. All information contained herein is confidential and may not be used in whole or in part without written permission from the owner.</p> <p>LCG Products are held to the governing ASTM, and CSA specification &amp; tolerances.</p>	