



Notes:

1. Lawn drains manufactured to ASTM C478 specifications.
2. Minimum concrete strength: 35 MPa.
3. 2 - Ø250mm cores & 1 - Ø125mm core provided.
4. Supplied with 75mm thick cast in base.
5. Groove end at rim accepts TR27 Cast Iron Grate.
6. Risers available: 150, 300, 450, 600mm heights.
7. Designed to suit installation in Drain Rock Trench
8. Drain Rock Trench details to be supplied by Project Engineer.
9. All dimensions are in millimeters.



Quality Assurance of products manufactured by The Langley Concrete Group has been verified by the following third party certification programs:



The **LANGLEY CONCRETE** Group of Companies

www.langleyconcretegroup.com

DESCRIPTION:

Ø450 Rock Drain

DRAWN BY: JAO

JOB NO.: N/A

CHK BY: KS

DWG NO: LB-450RD

DATE: Feb. 5, 2014

REV. BY: CC
Aug. 13, 2018

SCALE: 1:16

This drawing is the property of the Langley Concrete Group of Companies. All information contained herein is confidential and may not be used in whole or in part without written permission from the owner.

LCG Products are held to the governing ASTM, and CSA specification & tolerances.

LANGLEY (604) 533-1656 VICTORIA (250) 478-9581 CHILLIWACK 1-800 667-9600