






| PART LIST | | | |
|-----------|-----|-----------------------------|----------------------------|
| ITEM | QTY | PART NUMBER | WEIGHT |
| 1 | 1 | 3152 Vault - Bottom Section | 6,650 kg. |
| 2 | 1 | 3152 Vault - Top Section | 6,800 kg. w/ Clear Opening |

- Notes:
- 3152 Reinforced concrete water meter chamber is built as shown.
 - Unit designed to withstand AASHTO HS20 / BCL-625 live loading.
 - Concrete vault designed for the following earth covers:
 - Minimum: 0 m.
 - Maximum: 2.5 m.
 - Unit supplied with opening for access as required.
 - Unit supplied with cores for inlet/outlet as required.
 - Unit supplied with lifting insert as required.
 - Bottom chamber supplied with trench complete w/ grate as shown.
 - Unit supplied with $\varnothing 102$ mm drainage hole as shown.
 - Minimum rebar yield strength: 414 MPa.
 - Minimum concrete strength: 35 MPa.
 - Vault interior can be supplied with white paint for improved visibility/cleanliness and dampproofed exterior using CS-55 or approved equivalent.
 - All dimensions are in millimeters.



Langley Concrete Group is a certified Q-Cast Plant, an American Concrete Pipe Association Third Party Certification for the manufacture of Pipe, Manhole, Box Culvert & Precast Items.



Quality Assurance of products manufactured by The Langley Concrete Group has been verified by the following third party certification programs



All Dimensions are in Millimeters. Unless otherwise Stated

Projection Method: THIRD ANGLE



This drawing is the property of the Langley Concrete Group of Companies. All information contained herein is confidential and may not be used in whole or in part without written permission from the owner






DESCRIPTION:

3152
Water Meter Chamber

| | |
|-----------------------|--------------------|
| DRAWN BY: SR | JOB NO. |
| CHK BY: KS | DWG NO: 3152-WM |
| DATE: Aug.17, 2018 | |
| SCALE: 1:35 | |
| SIZE 11 x 17 | REV. |
| | SHEET 1 OF 1 |

| PART LIST | | | |
|-----------|-----|-----------------------------|-----------|
| ITEM | QTY | PART NUMBER | WEIGHT |
| 1 | 1 | 3152 Vault - Bottom Section | 6,650 kg. |
| 2 | 1 | 3152 Vault - Top Section | 6,800 kg. |

- Notes:
- 3152 Reinforced concrete water meter chamber is built as shown.
 - Unit designed to withstand AASHTO HS20 / BCL-625 live loading.
 - Concrete vault designed for the following earth covers:
 - Minimum: 0 m.
 - Maximum: 2.5 m.
 - Unit supplied with opening for access as required.
 - Unit supplied with cores for inlet/outlet as required.
 - Unit supplied with lifting insert as required.
 - Bottom chamber supplied with trench complete w/ grate as shown.
 - Unit supplied with $\varnothing 102$ mm drainage hole as shown.
 - Minimum rebar yield strength: 414 MPa.
 - Minimum concrete strength: 35 MPa.
 - Vault interior can be supplied with white paint for improved visibility/cleanliness and dampproofed exterior using CS-55 or approved equivalent.
 - All dimensions are in millimeters.



Langley Concrete Group is a certified Q-Cast Plant, an American Concrete Pipe Association Third Party Certification for the manufacture of Pipe, Manhole, Box Culvert & Precast Items.



Quality Assurance of products manufactured by The Langley Concrete Group has been verified by the following third party certification programs



All Dimensions are in Millimeters. Unless otherwise Stated

Projection Method: THIRD ANGLE



This drawing is the property of the Langley Concrete Group of Companies. All information contained herein is confidential and may not be used in whole or in part without written permission from the owner

DESCRIPTION:

3152
Water Meter Chamber
with Triple Door

DRAWN BY:
SR

JOB NO.

CHK BY:
KS

DWG NO:
3152-WM-2.0

DATE:
Aug.17, 2018

SCALE:
1:35






SIZE
11 x 17

REV.

SHEET 1 OF 1

| PART LIST | | | |
|-----------|-----|-----------------------------|--------------------------|
| ITEM | QTY | PART NUMBER | WEIGHT |
| 1 | 1 | 3152 Vault - Bottom Section | 6,650 kg. |
| 2 | 1 | 3152 Vault - Top Section | 6,800 kg. |
| 3 | 1 | 2121 Collar | 690 kg. w/ Clear Opening |

- Notes:
- 3152 Reinforced concrete water meter chamber is built as shown.
 - Unit designed to withstand AASHTO HS20 / BCL-625 live loading.
 - Concrete vault designed for the following earth covers:
 - Minimum: 0 m.
 - Maximum: 2.5 m.
 - Unit supplied with opening for access as required.
 - Unit supplied with cores for inlet/outlet as required.
 - Unit supplied with lifting insert as required.
 - Bottom chamber supplied with trench complete w/ grate as shown.
 - Unit supplied with $\varnothing 102$ mm drainage hole as shown.
 - Minimum rebar yield strength: 414 MPa.
 - Minimum concrete strength: 35 MPa.
 - Vault interior can be supplied with white paint for improved visibility/cleanliness and dampproofed exterior using CS-55 or approved equivalent.
 - All dimensions are in millimeters.



Langley Concrete Group is a certified Q-Cast Plant, an American Concrete Pipe Association Third Party Certification for the manufacture of Pipe, Manhole, Box Culvert & Precast Items.



Quality Assurance of products manufactured by The Langley Concrete Group has been verified by the following third party certification programs



All Dimensions are in Millimeters. Unless otherwise Stated

Projection Method: THIRD ANGLE



This drawing is the property of the Langley Concrete Group of Companies. All information contained herein is confidential and may not be used in whole or in part without written permission from the owner

DESCRIPTION:

3152
Water Meter Chamber
with 2121 Collar

| | |
|-----------------------|------------------------|
| DRAWN BY: SR | JOB NO. |
| CHK BY: KS | DWG NO: 3152-WM-3.0 |
| DATE: Aug.17, 2018 | |
| SCALE: 1:35 | |
| SIZE 11 x 17 | REV. |
| | SHEET 1 OF 1 |